

Retrofit Cartridges for Competitive Systems

Retrofit Cartridges Range

The 3M Water Filtration line of filtration products are carefully designed to protect beverage equipment, provide consistent beverage quality, and ensure seamless beverage service.

The 3M Water Filtration retrofit cartridges upgrade the performance of existing competitive systems with the same premium performance and design characteristics.

The cartridge design offers simple change outs while minimising corrosion potential often seen in metallic housings.

The sanitary quick change design minimises contamination of the filtration media, while the compact design allows the unit to be installed conveniently behind the beverage unit or under a cabinet.

The housing is durable and shatter-resistant, minimising the potential for leaks.

Units are FDA, CFR-21 compliant for use in all food and beverage applications and are 3rd party certified for design and performance.

Premium carbon technologies are available for differing water conditions.



Features

- Graded density, compressed carbon block
- Chlorine taste and odour reduction
- Built-in scale inhibition (Retrofits for Hot Bev only)
- Micron ratings from 0.5 to 5

Benefits

- Does not require activation
- Extends contact time for maximum chlorine and sediment reductions
- Enhances beverage quality over the life of the filter
- Protects equipment from the harmful effects of hard water
- Provides seamless beverage service
- Maximum protection, long life and enhances beverage clarity

Retrofit Cartridges for Competitive Systems

Retrofit Cartridges

Model	Part No	Size	Micron Rating	Capacity litres	Flow Rate lpm	Claims						Replaces** (Everpure System)
						Chlorine Taste & Odour	Sediment	Cyst	Turbidity	Scale Inhibition	Scale Reduction	
Cold Beverage												
CS-25	70020017409	S	0.5	7,571	3.8	•	•	•	•			2C/4C
CFS9812X	70020002666	L	0.5	34,069	5.7	•	•	•	•			MC
CFS9812ELX	70020018498	E	0.5	52,996	6.3	•	•	•	•			MC/XC
CFS9106	70020017367	S	1	9,450	3.8	•	•					2C/4C
CFS9112	70020002567	L	1	37,854	5.7	•	•					MC
CFS9710	7002002559	S	5	7,571	5.7	•	•					2C/4C
CS-65	70020017193	S	5	9,085	3.8	•	•					2C/4C
CFS9720	70020017136	L	5	18,170	5.7	•	•					MC/2CB5/4CB5
Hot Beverage												
CS-24	70020017391	S	0.5	7,571	3.8	•	•	•	•	•		BH/4H
CFS9812X-S	70020002674	L	0.5	34,069	5.7	•	•	•	•	•		MH/L-2000
CFS9812ELX-S	70020018506	E	0.5	52,996	6.3	•	•	•	•	•		MH/L-4000
CS-14	70020017375	S	1	9,464	3.8	•	•			•		BH/4H
CFS9112-S	70020017219	L	1	37,854	5.7	•	•			•		MH/L-2000
CFS9710-S	70020002542	S	5	7,571	5.7	•	•			•		BH
CS-64	70020017185	S	5	9,085	3.8	•	•			•		4H
CFS9720-S	70020017128	L	5	18,170	5.7	•	•			•		MC/2CB5-S/4CB5-S
Drop ins												
CFS9005-IMF*	70020007871	-	N/A	N/A	5.7					•		IMF
CFS110-C20*	70020143597	-	5	N/A	N/A		•					Pre-Filter
Special												
EP Plug	FD000049995	-	N/A	N/A	N/A							Plug
Empty sanitising	70020115047	-	N/A	N/A	N/A							Sanitising Cartridge
SWC9135	70020015429	-	N/A	1,350 grains hardness capacity	1.91						•	750

* Suitable for Dual Port Filtration

** May not be a direct comparison in micron rating

S = Short sump(8'), L = Long sump(12'), E = Extended sump(18')

Installation Tips:

- Shut off downstream equipment prior to installation of the system.
- Do not exceed operating parameters for temperature or pressure.
- Do not install outdoors.
- For cold water use only.
- For commercial use only.
- To have maximum operating pressure of 125 psi and operating temperature of 38°C.

Do not install with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

EPA Establishment Number 070595-CT-001. All materials are FDA compliant with CFR title 21.

3M Water Filtration recommends scheduled maintenance and replacement of the filter cartridge(s) in order for the product to perform as advertised/sold.



Water Filtration 3M United Kingdom PLC

3M Centre,
Cain Road, Bracknell
Berkshire RG12 8HT
Tel: +44 (0) 1344 858000
Fax: +44 (0) 1344 858559
www.3M.com/waterfiltration

3M Ireland

3M House, Adelphi Centre
Upper Georges Street
Dun Laoghaire
Co. Dublin, Ireland
Tel: +353 1 280 3555
Fax: +353 1 280 3509

3M Europe NV/SA

Hermeslaan 7
1831 Diegem
Belgium
Tel: +32-2-7224500
Fax: +32-2-7224518
www.3M.com/waterfiltration

Please recycle. Printed in UK.
© 3M 2008. All rights reserved.
LTFSEUR0025 0808